



INDIGO LT: THE UNIVERSAL-PURPOSE AND TILTABLE TRANSPORTER

Thanks to its double-acting hydraulic system, the tiltable Indigo LT makes very small approach angles possible. As a result, this strong trailer is more than capable of transporting cherry pickers, excavators and other heavy machinery with limited ground clearance. This model is built as standard with a 3,500-kg gross loading capacity; its dimensions are a handy 410 x 184 cm. With a strong chassis and solid steel walls, this model can definitely take a knock or two!

The parabolic suspension system, which includes shock absorbers, a 120-cm high continuous tailgate, an extra strong jockey wheel, multiplex floor and 195/50 R13 C tyres are all provided as standard too.

Various options are available, including an aluminium profile floor, a wire-mesh rack, or dropsides, and transform your Indigo LT into a well-equipped and functional transporter!

**BRING
IT ON.**



STANDARDS, OPTIONS, AND ACCESSORIES



Standard: robust chassis which is completely welded and galvanised.



Standard: with TÜV certified load securing system and with Safety Steps on the sides.



Standard: 1000 daN (KG) each fixing point.



Standard: a drive on ramp consists of an open anti-slip grating profile the ramp is full-immersion galvanised and with springs.



Standard: a drive on ramp in one piece 1200 mm high, including 2 removable corner pillars and adjustable heavy duty fasteners.



Standard: a parabolic suspension system including shock absorbers.



Standard: with tyres 195/50 R13c with black rims.



Standard: a double functioning tilting system.



Standard: an extra reinforced tilting jockey.



Standard: floor supports when tilting.



Option: aluminium profile floor in stead of a multiplex floor.



Option: aluminium dropsides 30 cm de high on the sides and front.



Option: wire rack extension 75 cm high including walls 30 cm high. Total 105 cm high, removable.



Standard: 3500 kg Maximum Gross Weight.



Standard: Indigo LT as a tiltable double axle, dimension 410 x 184 cm.



All Hapert trailers have been provided with the TÜV certified load-securing system!

