

Closed temperature-controlled trailers
L-1 & L-2



HAPERT SAPPHIRE

BOX VAN TRAILERS

SAPPHIRE TEMPERATURE- CONTROLLED TRAILER: RELIABLE AND DURABLE



This low-noise Sapphire L temperature-controlled trailer features sublime insulating characteristics, thanks to the insulated roof, walls, and floor. The high-quality closed superstructure has been mounted onto a fully self-supporting substructure. As a result, it can be used for a wide range of purposes.

As a standard, this model has been provided with insulation panels with a thickness of 40 mm (comprising 2 polyester top layers) on the inside and on the outside, 2x wooden layers on the inside, and a core of insulation material. The trailer has been provided with stainless steel hinges and locks. On the front, a powerful refrigeration unit has been installed, with a robust housing. Also part of the standard equipment include: an extension cable with plug, interior lighting, and closable control panel.

In short, it is a very complete temperature-controlled trailer, which, thanks to its smooth, gel-coated exterior top layer can be excellently provided with commercial stickers. Your logo and advertising will be presented most favourably!

BRING IT ON.



STANDARDS, OPTIONS, AND ACCESSORIES



SAPPHIRE

CLOSED TRAILERS



Standard: welded and hot-dipped galvanised substructure for single-axled trailer.



Option: single-axle refrigerated trailers with a gross loading capacity of up to 1800 kg, and dimensions up to a maximum of 300 x 150 x 210 cm.



Standard: welded and hot-dipped galvanised substructure for tandem-axled trailer.



Option: twin-axle refrigerated trailers with a gross loading capacity of up to 3500 kg, and dimensions up to a maximum of 400 x 180 x 210 cm.



Standard: refrigeration unit 230/50Hz with a capacity of 1600W/2°C on the reinforced front, including extension cable.




Standard: refrigerated part on the inside including interior lighting.



Standard: 2 handgrips on the front.



Standard: Stainless steel hinges, locks, and fasteners.



Standard: high-quality stainless steel lock.



Standard: insulated doors with a thickness of 400 mm, provided with gel coating.



Standard: mudguard supports mounted for mounting of mudguards.



Standard: walls with gel coating, roof and floor with insulation with a thickness of 400 mm.



Option: specially cast coating on the floor and aluminium fenders.



Option: aluminium tread plate and fender mounted.



Option: sliding prop stands mounted.



Option: heavy-duty telescoping supports (swivelling and adjustable) including crank.



Option: LED-Lighting.



WWW.HAPERT.COM